

## 厦门傲蓝环保产品技术参数 Xiamen Vablue Environmental Product Technical Specification Sheet

产品编号/Code	PPS-A550SG
产品描述/Description	聚苯硫醚针刺毡滤料Scrim-supported PPS needlepunched felt
纤维成分/Fiber Composition	100%PPS纤维/100% PPS fiber
基布成分/Scrim Composition	100%PPS纤维基布/PPS spun-yarn scrim

技术性能	公制单位	标准/范围	化学特性	
Item	Metric Unit	Target/Range	Chemical Properties	
平方克重 /Weight	g/m <sup>2</sup>	550	耐酸性/Acids Resistance	1
厚度 /Thickness	mm	1.9	耐碱性/Alkalis Resistance	1
密度 /Density	g/cm <sup>3</sup>	0.29	耐水解性/Hydrolysis Resistance	1
透气量 /Air Permeability	L/dm <sup>2</sup> /min	150	抗氧化性/Oxidize Resistance	4
断裂强度-纵向/Tensile Strength-MD	N/5 cm	800	抗有机溶剂/Organic solvents Resistance	1
断裂强度-横向/Tensile Strength-CD	N/5 cm	1000	耐磨性/ Abrasion Resistance	2
伸长@50N/5cm-纵向		0.03		
伸长@50N/5cm-横向		0.03		
热收缩 /Hot shrinkage		2%		
顶破强度 /Burst Strength	N/cm <sup>2</sup>	304		
连续工作温度 /Max Operation Temperature		160		
瞬间工作温度 /Min Operation Temperature		190		
后处理/Treatment	热定型、烧压			

### 备注/NOTE

1极好Excellent, 2好 Good, 3一般 Fair, 4差 Poor

以上产品严格按照国家技术指标及质量标准生产

This product is manufactured strictly based on GB specification and quality standard.

以上技术参数厦门傲蓝环保公司为平均测试参数, 仅供参考

Above data are the averages obtained from a series of typical by vablue and are just for reference

厦门傲蓝环保设备有限公司

Xiamen Vablue Environmental Equipment Co., Ltd.

中国厦门市同安区洪塘工业园洪塘路 233号, 361100

Tel: 86 (592)7100570

Fax: 86 (592) 7100209

www.vablue.com