

厦门傲蓝环保产品技术参数

Xiamen Vablue Environmental Product Technical Specification Sheet

产品编号/Style PTFE聚四氟乙烯/特氟龙针刺毡 (1um)
 产品描述/Description 有基布PTFE针刺液体过滤材料
 scrim-supported PTFE needlepunched felt(Liquid filtration)
 纤维成分/Fiber Composition 100%聚四氟乙烯纤维/PTFE

技术性能 Item	公制单位 Metric Unit	标准/范围 Target/Range	测试方法 Test Method
单位重量/Weight per unit area	g/m ²	750/720~780	ASTM D 461-93
厚度/Thickness	mm	1.0~1.2	ASTM D 461-93
透气量/Air Permeability	l/dm ² /min	60-100	ASTM D 737-96
顶破强度/Burst Strength	N/cm ²	201min	ASTM D 461-93
断裂强度/Tensile Strength	N/5 cm		
经向/MD		> 700	ASTM D 461-93
纬向/CD		> 700	ASTM D 461-93
表面后处理/Surface treatment	单面烧毛/Singed one side		
化学特性	等级 (1优、2良、3一般、4差)		
Chemical Properties	Rank		
耐酸性/Acids Resistance	1		
耐碱性/Alkalis Resistance	1		
耐水解性/Hydrolysis Resistant	1		
抗氧化性/Oxidize Resistance	1		
抗有机溶剂/Organic solvents	1		
耐磨性/ Abrasion Resistance	2		

以上产品严格按照国家技术指标及质量标准生产

This product is manufactured strictly based on GB specification and quality standard.

以上技术参数厦门傲蓝环保公司为平均测试参数，仅供参考

Above data are the averages obtained from a series of typical by vablue and are just for reference

厦门傲蓝环保设备有限公司
 Xiamen Vablue Environmental Equipment Co., Ltd.
 中国福建厦门市同安区洪塘工业区洪塘里233号, 361100
 Tel: 86 (592)7100570
 Fax: 86 (592) 7100209
 www.vablue.com